



Key features

- Meet UL, CE certification requirements
- Low ripple and noise
- Over load protection ,short circuit protection
- High efficiency, high density, fine quality and low price
- Industrial/military design
- Six sides metal shielding, international standard pin
- 100% test and work
- 3 Years product warranty

Electrical specifications

Model	Input voltage	Output Power(W)	Output voltage(V)	Output current(A)	Ripple(mv)	Efficiency (%)
DPM20-12S03	12(9-18)	13.2	3.3	4	100	80%
DPM20-12S05		20	5.0	4	100	83%
DPM20-12S12		20	12.0	1.66	100	84%
DPM20-12S15		20	15.0	1.33	100	85%
DPM20-12S24		20	24.0	0.83	50	86%
DPM20-12D12		20	±12	0.83	50	83%
DPM20-12D15		20	±15	0.66	50	84%
DPM20-24S03	24(18-36)	13.2	3.3	4	100	80%
DPM20-24S05		20	5.0	4	100	83%
DPM20-24S12		20	12.0	1.66	100	84%
DPM20-24S15		20	15.0	1.33	100	85%
DPM20-24S24		20	24.0	0.83	50	86%
DPM20-24D12		20	±12	0.83	50	83%
DPM20-24D15		20	±15	0.66	50	84%
DPM20-48S03	48(36-72)	13.2	3.3	4	100	80%
DPM20-48S05		20	5.0	4	100	83%
DPM20-48S12		20	12.0	1.66	100	84%
DPM20-48S15		20	15.0	1.33	100	85%
DPM20-48S24		20	24.0	0.83	50	86%
DPM20-48D12		20	±12	0.83	50	83%



DPM20-48D15		20	±15	0.66	50	84%
DPM20-110S03	110(70-140)	13.2	3.3	4	100	80%
DPM20-110S05		20	5.0	4	100	83%
DPM20-110S12		20	12.0	1.66	100	84%
DPM20-110S15		20	15.0	1.33	100	85%
DPM20-110S24		20	24.0	0.83	50	86%
DPM20-110D12		20	±12	0.83	50	83%
DPM20-110D15		20	±15	0.66	50	84%
DPM30-12S03		12(9-18)	13.2	3.3	6	100
DPM30-12S05	30		5.0	6	100	84%
DPM30-12S12	30		12.0	2.5	100	85%
DPM30-12S15	30		15.0	2	100	85%
DPM30-12S24	30		24.0	1.25	50	86%
DPM30-12D12	30		±12	1.25	50	83%
DPM30-12D15	30		±15	1	50	84%
DPM30-24S03	24(18-36)		13.2	3.3	6	100
DPM30-24S05		30	5.0	6	100	84%
DPM30-24S12		30	12.0	2.5	100	85%
DPM30-24S15		30	15.0	2	100	85%
DPM30-24S24		30	24.0	1.25	50	86%
DPM30-24D12		30	±12	1.25	50	83%
DPM30-24D15		30	±15	1	50	84%
DPM30-48S03		48(36-72)	13.2	3.3	6	100
DPM30-48S05	30		5.0	6	100	84%
DPM30-48S12	30		12.0	2.5	100	85%
DPM30-48S15	30		15.0	2	100	85%
DPM30-48S24	30		24.0	1.25	50	86%
DPM30-48D12	30		±12	1.25	50	83%
DPM30-48D15	30		±15	1	50	84%
DPM30-110S03	110(70-140)		13.2	3.3	6	100
DPM30-110S05		30	5.0	6	100	84%
DPM30-110S12		30	12.0	2.5	100	85%
DPM30-110S15		30	15.0	2	100	85%
DPM30-110S24		30	24.0	1.25	50	86%
DPM30-110D12		30	±12	1.25	50	83%
DPM30-110D15		30	±15	1	50	84%

Electrical specifications